

| Item | MMH112 | MM112 |
|--------------------------------|---|-------------------------|
| TV System | EIA | |
| Image Sensor | 1/4" Interline Transfer CCD | |
| Effective Picture Element | 768(H) x 492(V) pixels | 510(H) x 492(V) pixels |
| Sync. System | INT | |
| Sync. Frequency | (H) : 15.734KHz | |
| | (V) :59.94Hz | |
| Resolution(Horizontal) | 560 TVL | 380 TVL |
| S/N Ratio | More than 50dB | |
| Minimum Illuminance | Less than 0.2lx (F1.2) | Less than 0.1 lx (F1.2) |
| Gamma | 0.45 | |
| Video Output | 1.0Vp-p/75Ω | |
| White Balance | N/A | |
| Iris control DC Iris AES | Electric Shutter 1/60 sec. fixed | |
| | 1/60 - 1/100,000 sec | |
| Day and Night switching | N/A | |
| Power Source | DC12.0V±10% | |
| Power Consumption | Less than 0.9W | |
| Ambient Temp.(Operation) | -10□ □ 50□ | |
| Ambient Temp.(Storage) | -20□ □ 60□ | |
| Ambient Humidity(Operation) | Less than 80% (No condensation) | |
| Ambient Humidity(Storage) | Less than 90% (No condensation) | |
| Available Lens Mount | Fixed Lens / Vari-Focal Lens / CS-mount Lens (more than F1.0) | |
| External Dimension | 32(W) × 32(H) mm x 1 | |
| Weight | Less than 10g (Excl. lens holder and cables) | |
| DIP Switch | 1.AGC On/Off, 2.DC Iris/AES, 3.BLC On/Off, 4. LL/INT | |
| DC Iris Level Control | Provided | |



| Item | MMH212 | MM212 |
|--------------------------------|---|-------------------------|
| TV System | CCIR | |
| Image Sensor | 1/4" Interline Transfer CCD | |
| Effective Picture Element | 752(H) x 582(V) pixels | 500(H) x 582(V) pixels |
| Sync. System | INT | |
| Sync. Frequency | (H) : 15.625KHz | |
| | (V) :50.00Hz | |
| Resolution(Horizontal) | 560 TVL | 380TVL |
| S/N Ratio | More than 50dB | |
| Minimum Illuminance | Less than 0.2lx (F1.2) | Less than 0.1 lx (F1.2) |
| Gamma | 0.45 | |
| Video Output | 1.0Vp-p/75Ω | |
| White Balance | N/A | |
| Iris control DC Iris AES | Electric Shutter 1/50 sec. fixed | |
| | 1/50 - 1/100,000 sec | |
| Day and Night switching | N/A | |
| Power Source | DC12.0V±10% | |
| Power Consumption | Less than 3.2W | |
| Ambient Temp.(Operation) | -10□ □ 50□ | |
| Ambient Temp.(Storage) | -20□ □ 60□ | |
| Ambient Humidity(Operation) | Less than 80% (No condensation) | |
| Ambient Humidity(Storage) | Less than 90% (No condensation) | |
| Available Lens Mount | Fixed Lens / Vari-Focal Lens / CS-mount Lens (more than F1.0) | |
| External Dimension | 32(W) × 32(H) mm x 1 | |
| Weight | Less than 10g (Excl. lens holder and cables) | |
| DIP Switch | 1.AGC On/Off, 2.DC Iris/AES, 3.BLC On/Off, 4. LL/INT | |
| DC Iris Level Control | Provided | |

