



DESCRIPTION

The P3AC24-4-4W is a CCTV power center engineered to manage remote camera and accessory power requirements in a NEMA 4X weatherproof enclosure. The P3AC24-4-4W distribution module is designed with 4 individually fused outputs for powering up to 4 CCTV cameras and accessories.

It will provide 24Volts AC via distribution to four fused outputs with a total of 4.0 Amps continuous supply current.



FEATURES

- Convenient screw terminal and fuse access.
- Power ON/OFF switch.
- AC power LED indicator.
- Individual LED's for each fused output.
- Lightweight molded fiberglass NEMA 4X weatherproof enclosure.
- Uses easy to find automotive style fuses.
- Includes transformer and spare fuses.
- Available in 28VAC version.
- Available with optional circuit breaker, **P3AC24-4-4WCB**.

SPECIFICATIONS

- Input 115VAC 50/60 HZ; 0.9 Amps.
- Four 24VAC individually fused outputs.
- 4 Amps 100 VA supply current at 70°F.
- Output fuses are rated at 3 Amps.
- Main fuse is rated at 5 Amps.
- NEMA 4X weatherproof enclosure.
- Unit maintains camera synchronization.
- Transformer: 110VAC/24VAC, 100VA.
- Enclosure dimensions: 12" (H) x 10" (W) x 6" (D).