

REQUEST TO EXIT STATIONS

SQUARE PUSHBUTTONS

MODEL TS-2

- GREEN 2" SQUARE PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY SWITCH ACTION
- S.P.D.T. CONTACTS RATED 10 AMP. @ 35 VDC OR 120 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 2.5 INCHES
- ILLUMINATED WITH 25,000 HOUR REPLACEABLE BULB, (P/N 658), OPERATES ON 12 OR 24 VAC OR VDC
- UL APPROVED AND CSA CERTIFIED COMPONENTS



SPECIFY
MODEL TS-2-2
FOR D.P.D.T.
SWITCH

MODEL TS-4


- BLUE 2" SQUARE PUSHBUTTON
- LABELED WITH A.D.A. SYMBOL
- MOMENTARY ACTION SWITCH
- S.P.D.T. CONTACTS RATED 10 AMP. @ 35 VDC OR 120 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 2.5 INCHES
- ILLUMINATED WITH 25,000 HOUR REPLACEABLE BULB, (P/N 658), OPERATES ON 12 OR 24 VAC OR VDC
- UL APPROVED AND CSA CERTIFIED COMPONENTS



SPECIFY
MODEL TS-5
FOR 1/2" RED
LED

MODEL TS-2T BUILT-IN TIMER

- SAME SPECIFICATIONS AS TS-2
- 30 SECOND S.P.D.T. TIMED OUTPUT
- CONTACTS RATED 2 AMP. @ 35 VDC OR 120 VAC
- 30 SECOND TIMER WILL ACTIVATE WHEN SWITCH IS DEPRESSED. SUBSEQUENT DEPRESSIONS OF THE SWITCH BEFORE 30 SECONDS WILL RE-START THE TIMER.
- AN ADDITIONAL S.P.D.T. MOMENTARY OUTPUT IS AVAILABLE ON MODELS TS-2-2T, TS-3-2T, TS-4-2T, TS-5-2T
- MOMENTARY CONTACT RATING IS 10 AMP. @ 35 VDC OR 120 VAC



**OTHER MODELS
WITH TIMER**
TS-3T, TS-4T,
TS-5T, TS-2-2T,
TS-3-2T, TS-4-2T,
TS-5-2T

MODEL TS-30

- GREEN 2" SQUARE PUSHBUTTON
- LABELED "PUSH TO OPEN"
- MOMENTARY ACTION SWITCH
- S.P.D.T. CONTACTS RATED 10 AMP. @ 35 VDC OR 120 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 2.5 INCHES
- ILLUMINATED WITH 25,000 HOUR REPLACEABLE BULB, (P/N 658), OPERATES ON 12 OR 24 VAC OR VDC
- UL APPROVED AND CSA CERTIFIED COMPONENTS



SPECIFY
MODEL TS-30-2
FOR D.P.D.T.
SWITCH

MODEL TS-3

- GREEN 2" SQUARE PUSHBUTTON
- BRIGHT 1/2" RED LED, 12 OR 24 VAC/DC
- LABELED "PUSH TO EXIT"
- MOMENTARY SWITCH ACTION
- S.P.D.T. CONTACTS RATED 10 AMP. @ 35 VDC OR 120 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 2.5 INCHES
- ILLUMINATED WITH 25,000 HOUR REPLACEABLE BULB, (P/N 658), OPERATES ON 12 OR 24 VAC OR VDC
- UL APPROVED AND CSA CERTIFIED COMPONENTS



SPECIFY
MODEL TS-3-2
FOR D.P.D.T.

MODEL TS-40

MEETS THE BOCA CODE FOR ACCESS CONTROLLED EGRESS DOORS

- GREEN 2" SQUARE PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- 30 SECOND S.P.D.T. TIMED CONTACTS RATED 2 AMP. @ 35 VDC OR 120 VAC
- MOMENTARY CONTACTS S.P.D.T., RATED 10 AMP. @ 35 VDC OR 120 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 2.5 INCHES
- UL APPROVED AND CSA CERTIFIED COMPONENTS

